



DIY Waterproofing and Damp-proofing solutions.

FROGSKIN™

Dirt & Water resistant Roof Paint

Discussion

FROGSKIN is an environmentally-friendly, latest generation Acrylic Terpolymer roof paint for use on metal and tiled roofs. FROGSKIN is specifically designed to dramatically increase adhesion to the roof substrate as well as ensure lasting colour fastness, providing long-term stability and non-fading beauty. Using the waterproofing principles perfected in the Flash Harry laboratory, FROGSKIN's formulation ensures minimal water uptake, thereby eliminating delamination as well as dramatically reducing dirt collection. When used strictly in accordance with the manufacturer specifications and subject to our terms and conditions, FROGSKIN roof paint is covered by our 8-year quality guarantee.

FROGSKIN is available in 20L and 5L containers and in a range of eight different colours.

Physical Properties

Colour:	Red, Grey, Black, Brown, Burgundy, Charcoal, Terracotta and Green.
Application:	Brush, roller or spray.
Coverage:	6-8/m ² (depending on surface porosity)
Total Solids:	+/- 50%
Specific Gravity:	+/- 1.2
Viscosity:	95-105 Krebs Units at 25°C
Drying Time:	(Between Coats) Minimum 30 minutes at 25°C at 65% R.H. (Last Coat) 2-3 hours before resistant to rain. Full cure 12-20 hours at 25°C at 65% R.H.
Cleaning:	Water when wet. Ethyl acetate when dry.
Flammability:	Non Flammable

TECHNICAL DATA SHEET



DIY Waterproofing and Damp-proofing solutions.

Surface preparation

Cleaning of Surfaces

Remove all dust, dirt, loose and flaking material or any other barrier to adhesion from the surface on which the product will be applied; and

All substrates must be dry, clean and free of oil for the product to be successfully applied.

Priming of Surfaces

Priming of Iron Roofs

New iron surfaces need to be fully degreased and cleaned, removing all traces of oil, dirt, dust or other contaminants or materials.

Prime the entire surface with Flash Harry Galvanized Iron Primer.

Rusted surfaces need to be abraded back to a bright metal surface, free of rust and then primed with Flash Harry Galvanized Iron Primer.

Previously painted iron roofs should be cleaned with a high pressure water jet, removing all loose and flaking paint and left to dry and then primed with Flash Harry Galvanized Iron Primer.

Priming of Tiled Roofs

After proper cleaning, all porous and granular surfaces should be sealed with Flash Harry Stormcryn Primer.

Previously painted tiled roofs should be cleaned with a high pressure water jet, removing all loose and flaking paint and left to dry and then primed with Flash Harry Stormcryn Primer.

Coating of Surfaces

Application with brush, roller or airless spray.

Stir contents thoroughly using a flat paddle.

Apply the first undiluted coat at a rate of 6-8m²/L and allow a minimum of 6 hours to dry.

Apply the second undiluted coat at a rate of 6-8m²/L and allow a minimum of 6 hours to dry

Clean with water.

TECHNICAL DATA SHEET



DIY Waterproofing and Damp-proofing solutions.

Important Notes

Do not apply FROGSKIN roof paint if rain is imminent as any rainfall or water will adversely affect the cohesive or bonding nature of the product during the time period required for drying of the product.

Do not dilute FROGSKIN roof paint in any manner whatsoever.

FROGSKIN roof paint will be resistant to light rain after 6 hours.

Curing and bonding time depends on humidity and ambient temperature.

During winter months do not apply FROGSKIN roof paint early in the morning when dew and frost may be present. Do not continue to apply in the late afternoon as temperatures begin to fall, especially on iron roof applications as this will have a negative effect on the adhesive or bonding nature of the product

During the summer months do not apply FROGSKIN roof paint during mid-day hours when surface temperatures exceed 50°C, as this will also have a negative effect on the adhesive or bonding nature of the product.

Do not use to overcoat bitumen waterproofing systems.

Do not use for slate roof applications.

Not recommended or suitable for flat roof applications.

Raw fibre-cement surfaces should be properly cleaned and then primed with Flash Harry Stormcryl Primer before this product is applied.

To ensure colour consistency, ensure that all products used by the consumer share the same batch number.

FROGSKIN 8 Year guarantee

The FROGSKIN guarantee applies when the consumer has registered this guarantee at www.frogskinpaint.co.za within a period of 60 days from date of purchase from an approved or recognised supplier, distributor or retailer and has fully and properly followed the terms and conditions of this guarantee

Failing to do this, will automatically disqualify and exclude the consumer from the guarantee.