



DIY Waterproofing and Damp-proofing solutions.

Plaster's Pal Bondingliquid

Discussion

PLASTER'S PAL is a high performance easy to use water based bonding liquid, used as a surface treatment as well as an admixture. PLASTER'S PAL improves adhesion of cement and Gypsum plasters to smooth impervious surfaces, face brick, plaster board, painted surfaces and a number of other building substrates. As an admixture in plaster, cement, tile grouts, tile adhesives, PVA paints it improves adhesion and improves water resistance. PLASTER'S PAL is available in 25L, 5L and 1L containers.

Physical Properties

Colour:	White milky liquid
Application:	Brush, roller or spray.
Coverage:	8-10m ² /L depending on surface porosity
Total Solids:	+/- 20%
Specific Gravity:	+/- 1
Viscosity:	<10 Krebbs Units at 25°C
Cleaning:	Warm soapy water
Flammability:	Non Flammable



DIY Waterproofing and Damp-proofing solutions.

Surface preparation

All forms of surface contamination must be removed to ensure a smooth surface, free of moisture and any loose material, or any other barrier to adhesion.

Technical assistance and applicator training are freely available to all approved users.

Application

On rough, surfaces or if applying gypsum plaster.

Apply the PLASTER'S PAL by means of a brush or roller. Plaster in the normal manner over the PLASTER'S PAL while it is still **wet**. PLASTER'S PAL can be added to the plaster (10% water replacement) to improve the final bond.

On smoother problematic surfaces or if applying thick section of plaster

Apply the PLASTER'S PAL by means of a brush or roller. While the PLASTER'S PAL is still **wet** apply a thin "slush coat" (1 part cement, 2 parts sand and 10% PLASTER'S PAL water replacement) by means of a block brush or Terylene machine. Allow the slush coat to dry and then plaster in the usual manner.

Coverage

aprox 8 – 10 square meters per litre. Coverage does depend on the porosity of the substrate.

As an admixture

As a 10% - 20% water replacement PLASTER'S PAL improves adhesion, Water resistance, cohesive strength, toughness and flexibility in plaster, cement, tile grouts, tile adhesives and PVA paints.

Note: The use of PLASTER'S PAL does not render grouts and plasters waterproof. For that application see Flash Harry HYPERCRETE.

Do not apply onto wet surfaces.

Do not apply if rain is imminent

Clean up with warm soapy water