



ROOF TILE & RIDGE REPAIR

RUBBERISED WATERPROOF MORTAR PASTE



ROOF TILE & RIDGE REPAIR IS AN EXTRA THICK, HEAVY DUTY, HIGH BUILD, ADHESIVE FORMULA THAT ENCAPSULATES, BONDS AND WATERPROOFS. USED TO PROTECT, SEAL AND REPAIR DAMAGED AND CRACKED CONCRETE ROOF TILES, RIDGES AND TILE JOINTS. **ROOF TILE & RIDGE REPAIR** HAS A 12 YEAR GUARANTEE. FOR MORE INFORMATION, PLEASE REFER TO THE TERMS AND CONDITIONS - WWW.FLASHHARRY.CO.ZA.



APPLICATIONS

Used to protect, seal and repair damaged and cracked concrete roof tiles, ridges and tile joints.



FOR GLUEING
CRACKED
RIDGE MORTAR



CRACKED TILES , TILE
JOINTS & ROOF
RIDGES



FOR WATERPROOFING
AROUND CHIMNEYS AND
SKYLIGHTS



USE AS A MAINTENANCE
COAT ON EXISTING
ACRYLIC WATERPROOFING
SYSTEMS





PRIMING

- **Priming** - Porous surface should be primed with **Flash Harry Roof Bond Primer** bonding liquid or a 50% diluted coat of **Roof Tile & Ridge Repair**. On Fibre Board applications use **with Flash Harry Bitucryl Primer**.
- **Previously Painted Surfaces** - **Roof Tile & Ridge Repair** can be applied onto dry, sound, clean and well adhered acrylic roof coatings.



IMPORTANT NOTES

- For bridging gaps, flashing and other areas of extreme movement use traditional **Flash Harry Liquid Plastic** in conjunction with a waterproofing membrane.
- **Not recommended for under tiles or areas of permanent ponding**
- **Not recommended for lightweight screed applications**
- **Not recommended for Slate roof applications**
- **Not recommended to overcoat existing bitumen systems**
- **Do not apply if rain is imminent.**
- **Application Temperature:** Do not apply on surfaces less than 5°C or more than 35°C
- Curing time depends application thickness as well as the humidity and air temperatures.
- Use water to clean hands and tools



MAINTENANCE

It is advisable to overcoat the waterproofing system every 5 years.



APPLICATION

STEP 1

PREPARATION

Ensure all surfaces are dry and thoroughly cleaned, removing all dust, dirt, grime and any other soiling agents. On parapets and painted roofs, a wire brush should be used to remove all loose or peeling paint until a sound surface is achieved.





STEP 2

STIR WELL

1st coat. Generously apply Roof Tile & Ridge Repair using of a stiff waterproofing brush or trowel. Roof Tile & Ridge Repair can be used as a glue, behind loose existing mortar, to fix back into place.

STEP 3

Allow 2 hours drying.

Apply a generous 2nd coat ensuring an even wet film thickness filling all gaps cracks and voids.

Coverage depends on application thickness.

Roof Tile & Ridge Repair can be overcoated with **Flash Harry Frogskin Roof Paint** or any good quality decorative paint.



PACKAGING AND COLOURS

Roof Tile & Ridge Repair is available in 5L containers and in Grey.



PHYSICAL PROPERTIES

Colour:	Grey.
Application:	Scraper or putty knife.
Coverage:	Coverage depends on application thickness
Total Solids:	± 70%
Specific Gravity:	± 1.15
Viscosity:	Putty consistency
Drying Time:	Touch dry – 2 hour @ 25°C Hard dry – Depending on thickness - 48 hours @ 25°C (65% R.H.) Resistant to light rain after 6 hours @ 25°C (65% R.H.) Full cure - 7 days @ 25°C (65% R.H.)
Cleaning:	Water
Flammability:	Non-Flammable.





DATA SHEET



HEALTH AND SAFETY

- Avoid contact with skin or eyes.
- Keep out of reach of children.
- If accidentally swallowed, seek medical advice immediately.
- To avoid the risk of spillage, always store and transport containers in a secure upright position.
- Refer to Material Safety Data Sheet for additional information.



STANDARD DISCLAIMER

The recommendations contained herein are given in good faith and meant to guide the specifier or user in accordance with good painting practices. They are gained from our tests and experiences and are believed to be accurate and reliable. No warranty/guarantee is implied by the recommendations contained herein since the conditions of use; application method, substrate and cleanliness of the substrate are beyond **STT Sales (PTY) LTD** control.

Important Note; It is the responsibility of the user to ensure that the latest TDS is being used for reference. **FLASH HARRY** Data Sheets are available on our website www.flashharry.co.za or Email info@darachem.co.za.

Updated March 2024 (This supersedes all previous publications).

