



FROGSKIN ROOF BOND PRIMER

PENETRATING AND STABILISING
BONDING LIQUID



FROGSKIN ROOF BOND PRIMER HAS EXCELLENT PENETRATING, BINDING AND ADHESIVE PROPERTIES MAKING IT SUITABLE FOR BOTH INTERIOR AND EXTERIOR APPLICATIONS. WHETHER APPLIED TO POWDER, FRIABLE, POROUS, NEW OR WEATHERED SURFACES, IT CREATES AN ALKALINE-RESISTANT FINISH WHICH DRAMATICALLY IMPROVES THE ADHESION OF **FROGSKIN ROOF PAINT**.

FROGSKIN ROOF BOND PRIMER HAS A 10 YEAR GUARANTEE. FOR MORE INFORMATION, PLEASE REFER TO THE TERMS AND CONDITIONS - WWW.FLASHHARRY.CO.ZA.



APPLICATIONS

For use on concrete roof tiles, granular roof tiles, raw plaster and fibre cement surfaces and applied to powdery, friable, porous, new or weathered surfaces





IMPORTANT NOTES

- **Do not** use water to thin this primer, as thinning will reduce adhesive properties.
- **Do not** mix with other products.
- Not for use under two-pack solvent or water-based products.
- **Do not** apply before 09h00 and after 16h00 in the winter.
- **Do not** apply if rain is imminent.



MAINTENANCE

It is advisable to overcoat the waterproofing system every 2-3 years.



APPLICATION

STEP 1

PREPARATION

Surface areas must be thoroughly cleaned and dried, removing any dust, algae, loose and flaking paint, dirt, grime and other soiling agents.

STEP 2

STIR WELL

Stir well with a flat paddle before use.

STEP 3

Once the surface is dry, apply one generous coat of **FROGSKIN Roof Bond Primer** to the area that needs painting, using either a brush or paint roller.

Allow to dry 4-6 hours before over coating with **FROGSKIN™ Roof Paint**.





PHYSICAL PROPERTIES

Colour:	White Milky Liquid.
Application:	Brush or roller or spray
Coverage:	10 - 12m ² /L (depending on surface porosity)
Total Solids:	± 20%
Specific Gravity:	± 1
Viscosity:	<10 Krebs Units at 25°C
Drying Time:	Allow to dry 4 – 6 hours before over coating with FROGSKIN Roof Paint
Cleaning:	Water
Flammability:	Non-Flammable.
Pack Size:	5L and 20L



HEALTH AND SAFETY

- Avoid contact with skin or eyes.
- Keep out of reach of children.
- If accidentally swallowed, seek medical advice immediately.
- To avoid the risk of spillage, always store and transport containers in a secure upright position.
- Refer to Material Safety Data Sheet for additional information.



STANDARD DISCLAIMER

The recommendations contained herein are given in good faith and meant to guide the specifier or user in accordance with good painting practices. They are gained from our tests and experiences and are believed to be accurate and reliable. No warranty/guarantee is implied by the recommendations contained herein since the conditions of use; application method, substrate and cleanliness of the substrate are beyond **STT Sales (PTY) LTD** control.

Important Note; It is the responsibility of the user to ensure that the latest TDS is being used for reference. **FLASH HARRY** Data Sheets are available on our website www.flashharry.co.za or Email info@darachem.co.za.

Updated February 2023 (This supersedes all previous publications).

