



DIY Waterproofing and Damp-proofing solutions.

Damp Doctor Facebrick and masonry sealer

Discussion

DAMP DOCTOR FACE BRICK and MASONRY sealer is an invisible, deep penetrating, weather resistant, water and dirt repellent, which seals brick, stone, concrete and mortar surfaces against penetrating rain, water from garden irrigation systems, taps or down pipes. On any porous, such as pre-cast concrete walls, DAMP DOCTOR FACE BRICK and MASONRY Sealer will prevent algae growth and subsequent discoloration. On raw plaster surfaces, DAMP DOCTOR FACE BRICK and MASONRY Sealer will dramatically improve the adhesion and coverage of decorative paints. DAMP DOCTOR FACE BRICK and MASONRY Sealer is available in 25L and 5L containers.

Physical Properties

Colour:	Clear
Application:	Brush, roller or spray.
Coverage:	4-6m ² /L
Total Solids:	+/- 12.5%
Specific Gravity:	+/- 1
Viscosity:	<10 Krebbs Units at 25°C
Drying Time:	Allow three hours drying time before over coating
Cleaning:	Warm soapy water
Flammability:	Non - Flammable



DIY Waterproofing and Damp-proofing solutions.

Surface preparation

All forms of surface contamination must be removed to ensure a smooth surface, free of moisture and any loose material, or any other barrier to adhesion. Use a wire brush to remove any laitance and efflorescence. Newly plastered surfaces should be fully cured before application.

Technical assistance and applicator training are freely available to all approved users.

Application

During application, ensure adequate eye protection (goggles).

Evenly apply by using a brush or low pressure knapsack sprayer. Always begin treating the surface from the highest point, working downwards.

Immediately apply a second coat onto the still wet first coat, also working from the top down. Wipe off any overspray on glass surfaces as well as window & door frames.

Be aware of wind direction during spray application.

To ensure second coat penetration, apply when first coat is still wet.

To achieve maximum penetration, avoid treating surfaces while warm and exposed to full sunlight.

Do not apply onto wet surfaces.

Do not apply prior to cementitious coatings.

Coverage – 4m² to 6m² per litre. Two coat application.

Clean up with warm soapy water.

Do not apply if rain is imminent.

Technical assistance and applicator training are freely available to all approved users.